

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name	Euromix™ NPS (Non-Porous Surface) Keycoat Render
Product Code	RENNPS
Supplier Name	Euromix Pty Ltd ABN 57 664 946 070
Address	31-33 Water Street, Strathfield South. NSW 2136
Telephone	02 9572 9061
Email	contact@euromix.com.au
Synonym(s)	Euro NPS, Euromix Keycoat, Euromix NPS Render, Euro Scratchcoat
Use(s)P	Pre-blended, acrylic modified, cement-based render that is suitable for decorative rendering and patching over most substrates for interior and exterior use.

2. HAZARDS IDENTIFICATION

This product is classified as hazardous according to Safe Work Australia criteria.
 Not classified as a dangerous good by the criteria of the ADG code, IMDG or IATA.

GHS Classifications

Skin Corrosion/Irritation:	Category 2
Skin Sensitization:	Category 1B
Series Eye Damage / Eye Irritation	Category 2A
Specific Target Organ Systemic Toxicity (Repeated Exposure):	Category 3

SIGNAL WORD

DANGER

Pictograms



Hazard statements

H315	Causes skin irritation.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H373	May cause damage to lungs and respiratory tract through prolonged or repeated exposure.

Prevention statements

P260	Do not breathe dust.
P264	Wash thoroughly after handling.
P271	Use only outdoors in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

Response statements

P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P304 + P340	IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P314	Get medical advice/attention if you feel unwell.
P321	Specific treatment is advised – see first aid instructions.
P362	Take off contaminated clothing and wash before reuse.

Disposal statements

P501	Dispose of contents/container in accordance with relevant regulations.
------	--

UN No	None Allocated	Hazchem Code	None Allocated	Pkg Group	None Allocated
DG Class	None Allocated	Subsidiary Risk(s)	None Allocated	EPG	None Allocated

3. COMPOSITION/INFORMATION ON INGREDIENTS

A small proportion of the fine dust associated with this product will contain 'Respirable Crystalline Quartz' (RCQ). While the product is wet and being applied as per the directions on the package the amount of airborne RCQ will be minimal, but it is still recommended that proper PPE is worn. Once dry any residues, grinding or strong abrasive forces may re-introduce RCQ into the air so caution should be taken.

Ingredient	Formula	Conc.	CAS No.
PORTLAND CEMENT	Not Available	20 - 50%	65997-15-1
HYDRATED LIME	Not Available	> 5%	1305-62-0
QUARTZ SANDS	Not Available	50 - 70%	68131-74-8
SYNTHETIC ADDITIVES	Not Available	5% - 10%	10101-41-4
CRYSTALLINE SILICA (QUARTZ)	SiO ₂	< 1%	14808-60-7
NON-HAZARDOUS INGREDIENTS	Not Available	Remainder	N/A

4. FIRST AID MEASURES

Eye	Flush thoroughly with flowing water for at least 15 minutes and seek medical attention if symptoms persist. If wet cement is splashed into the eyes, flush thoroughly with flowing water for 15 minutes and seek urgent medical attention.
Inhalation	Remove from dusty area to fresh air. If symptoms persist, seek medical attention. Apply artificial respiration if not breathing.
Skin	Remove heavily contaminated clothing immediately. Wash off skin thoroughly with water. A shower may be required. Seek medical attention for persistent irritation or burning of the skin or contact Poison Hotline on 13 11 26.
Ingestion	Rinse mouth and lips with water. Do not induce vomiting. Give water to drink to dilute stomach contents. If symptoms persist, seek medical attention.
Advice to Doctor	Treat for moderate to strong alkali and symptomatically.
First Aid Facilities	Eye wash station and safety shower should be available.

Additional Information - Aggravated Medical Conditions

Irritating to the eyes, skin and respiratory system. Chronic over exposure to silica quartz dust may result in silicosis (lung disease). Principal symptoms of silicosis are coughing and breathlessness. Some individuals may exhibit an allergic response upon exposure to this product, possibly due to the trace amounts of chromium present. Crystalline silica and hexavalent chromium compounds are classified as carcinogenic to humans (IARC Group 1).

Skin	Prolonged and repeated skin contact with cement in wet concrete, mortars and slurries may result in irritant dermatitis or alkaline burns.
Eye	Irritating to the eye. If wet cement is splashed into the eye, alkaline burns can cause permanent damage.

5. FIRE FIGHTING

Flammability	Non-flammable. Does not support combustion of other materials.
Fire and Explosion	No fire or explosion hazard exists.
Extinguishing	Non-flammable; use suitable extinguishing agent for surrounding fire.
Hazchem Code	None.

6. ACCIDENTAL RELEASE MEASURES

Spillage	If spilt (bulk), contact emergency services if appropriate. Wear dust-proof goggles, PVC/rubber gloves, a Class P2 respirator (where an inhalation risk exists), coveralls and rubber boots. Clear area of all unprotected personnel. Prevent spill entering drains or waterways. Collect and place in sealable containers for disposal or reuse. Avoid generating dust. Slippery when wet.
Emergency Procedures	Follow safety requirements for personal protection under Section 8 Exposure Controls/Personal Protection.

7. HANDLING AND STORAGE

Storage	Store off the floor in the original bags in a cool, dry, well ventilated area, removed from excessive moisture and heat. Ensure packages are adequately labelled, protected from physical damage, and sealed when not in use.
Handling	<p>Euromix NPS Keycoat is supplied in 15 kg bags. Recognised local safe lifting methods should be used.</p> <p>Before use, carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking, and smoking in contaminated areas.</p>
Property/ Environmental	Refer to Section 13.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ventilation	Do not inhale dust/powder. Use with adequate ventilation. Where a dust inhalation hazard exists, mechanical extraction ventilation is recommended. Maintain dust levels below the recommended exposure standard.
Exposure Standards	<p>PORTLAND CEMENT (655997-15-1) ES-TWA: 10 mg/m³ (Respirable Dust)</p> <p>SILICA, CRYSTALLINE – QUARTZ (14808-60-7) ES-TWA: 0.1 mg/m³ (Respirable Dust). Under Model WHS Law adopted in most Australian jurisdictions.</p>
PPE	Wear dust-proof goggles and rubber or PVC gloves. Where an inhalation risk exists, wear a Class P2 respirator. If there is potential for prolonged and/or excessive skin contact, wear coveralls. At high dust levels, wear a Class P3 respirator or a Powered Air Purifying Respirator (PAPR) with Class P3 filter.



9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Light grey in colour	Solubility (water)	< 10 g/L
Odour	Slight Odour	Specific Gravity	1.4 to 1.7 kg/l
pH	11-13	% Volatiles	Not Available
Vapour Pressure	Not Available	Flammability	Non-Flammable
Vapour Density	Not Available	Flash Point	Not Relevant
Boiling Point	Not Available	Upper Explosion Limit	Not Relevant
Melting Point	> 1200 °C	Lower Explosion Limit	Not Relevant
Evaporation Rate	Not Available	Autoignition Temperature	Not Available

10. STABILITY AND REACTIVITY

Chemical Stability	Chemically Stable under correct conditions of storage, considered inert in powdered and solid state.
Conditions to Avoid	Keep free of moisture.
Incompatible Materials	Incompatible with oxidising agents (e.g. hypochlorites), ethanol, acids (e.g. hydrofluoric acid) and interhalogens (e.g. chlorine trifluoride). Water contact may increase product to 2°C to 3°C.
Decomposition Products	Unlikely to evolve toxic gases when heated to decomposition.
Hazardous Reactions	None.

11. TOXICOLOGICAL INFORMATION

Acute Toxicity	No known toxicity data available for this product.
Eye	Irritant upon contact with dust. Over exposure may result in pain, redness, corneal burns and ulceration with possible permanent damage.
Inhalation	Irritating to the respiratory system, causing coughing and sneezing. Over exposure may result in severe mucous membrane irritation and bronchitis. Hexavalent chromium is reported to cause respiratory sensitisation. However, due to the trace amount present, a hazard is not anticipated under normal conditions of use. Crystalline silica can cause silicosis (lung disease) with chronic over exposure. However, due to low levels present and product application, adverse health effects are not anticipated.
Skin	Irritating to the skin. Prolonged and repeated contact with powder or wetted form may result in skin rash, dermatitis, and sensitisation.
Ingestion	Slightly corrosive. Ingestion may result in burns to the mouth and throat, with vomiting and abdominal pain. Due to product form, ingestion is not considered a likely exposure route.
Mutagenicity	Insufficient data available for this product to classify as a mutagen.
Carcinogenicity	This product contains crystalline silica which is classified as carcinogenic to humans (IARC Group 1). However, there is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis. Therefore, preventing the onset of silicosis will also reduce the cancer risk. Hexavalent chromium compounds are classified as carcinogenic to humans (IARC Group 1). However, due to the trace amounts present, the criteria for classification is not met.
Reproductive	Insufficient data available to classify as a reproductive toxin.
STOT – SE	Irritating to the respiratory system. Over exposure may result in irritation of the nose and throat, coughing. High level of exposure may result in breathing difficulties.
STOT – RE	Repeated exposure to respirable silica may result in pulmonary fibrosis. Silicosis is a fibronodular lung disease caused by deposition in the lungs of fine respirable particles of crystalline silica. Principal symptoms of Silicosis are coughing and breathlessness. In the wet state, the likelihood of an inhalation hazard is reduced.

12. ECOLOGICAL INFORMATION

Toxicity	Product forms an alkaline slurry when mixed with water. This product is non-toxic to aquatic life forms when present in cured solid form.
Persistence & Degradability	Product is persistent and would have a low degradability.
Mobility in soil	A low mobility would be expected in a landfill situation.

13. DISPOSAL CONSIDERATIONS

Waste Disposal	Reuse or recycle where possible. Alternatively, ensure product is covered with moist soil to prevent dust generation and dispose of to an approved landfill site. Contact the manufacturer for additional information (if required).
Legislation	Dispose of in accordance with relevant local legislation. Keep out of sewer and stormwater drains.

14. TRANSPORT INFORMATION

Not classified as a dangerous good by the criteria of the ADG Code.

Drivers of trucks transporting bagged product should ensure that the bags are properly restrained.

Shipping Name	None Allocated	Hazchem Code	None Allocated	Pkg Group	None Allocated
UN No	None Allocated	Subsidiary Risk(s)	None Allocated	EPG	None Allocated
DG Class	None Allocated				

15. REGULATORY INFORMATION

Poison Schedule AICS	A poison schedule number has not been allocated to this product using the criteria in the Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP). All chemicals listed on the Australian Inventory of Chemical Substances (AICS).
Hazard Codes	XI Irritant XI Harmful
Risk Phrases	R36/37/38 Irritating to eyes, respiratory system and skin.
R48/20 Harmful	Danger of serious damage to health by prolonged exposure through inhalation.
Safety Phrases	S22 – Do not breath dust.
S24/25	Avoid contact with skin and eyes.
S36/37	Wear suitable protective clothing and gloves.

16. OTHER INFORMATION

Additional Info

CEMENT CONTACT DERMATITIS: Individuals using wet cement, mortar, grout or concrete could be at risk of developing cement dermatitis. Symptoms of exposure include itchy, tender, swollen, hot, cracked or blistering skin with the potential for sensitisation. The dermatitis is due to the presence of soluble hexavalent chromium.

IARC – GROUP 1 – PROVEN HUMAN CARCINOGEN. This product contains an ingredient for which there is sufficient evidence to have been classified by the International Agency for Research into Cancer as a human carcinogen. The use of products known to be human carcinogens should be strictly monitored and controlled.

RESPIRATORS: In general, the use of respirators should be limited and engineering controls employed to avoid exposure. If respiratory equipment must be worn ensure correct respirator selection and training is undertaken. Remember that some respirators may be extremely uncomfortable when used for long periods. The use of air powered, or air supplied respirators should be considered where prolonged or repeated use is necessary.

PERSONAL PROTECTIVE EQUIPMENT GUIDELINES: The recommendation for protective equipment contained within this MSDS report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

HEALTH EFFECTS FROM EXPOSURE: It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare an MSDS report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

ABBREVIATIONS:

MSDS – Material Safety Data Sheet

mg/m³ – Milligrams per cubic metre

ppm – Parts Per Million

ES-TWA – Exposure Standard - Time Weighted Average

CNS – Central Nervous System

NOS – Not Otherwise Specified

pH – relates to hydrogen ion concentration – this value will relate to a scale of 0 – 14, where 0 is highly acidic and 14 is highly alkaline.

STOT SE – specific target organ toxicity (single exposure SE)

STOT RE – specific target organ toxicity (repeat exposure RE)

CAS# - Chemical Abstract Service Number – used to uniquely identify chemical compounds.

IARC – International Agency for Research on Cancer.

Report Status

This document has been compiled by Euromix Pty Ltd of the product and serves as the manufacturer's Material Safety Data Sheet.

While the information in this Material Safety Data Sheet has been prepared in good faith, Euromix Pty Ltd does not warrant that the information is accurate, complete, or up to date.

Contact Point

For further information on this product contact:

Telephone: 02 9572 9061
Emergency: 13 11 26 (Poison Information Line Australia)
Email: contact@euromix.com.au
Web site: www.euromix.com.au

Advice Note

The information in this document is believed to be accurate. Please check the currency of this MSDS by contacting:

02 9572 9061

or

www.euromix.com.au

Each user of any information, or any product referred to, in this Material Safety Data Sheet must:

- determine whether the information or product is suitable for their purpose;
- assess and control any risks associated with the information or product; and
- obtain professional advice in relation to the use of the information or product.

To the extent permitted by law, Euromix Pty Ltd:

- excludes all representations, warranties, and guarantees in relation to any information in this Material Safety Data Sheet; and
- will not be liable for any direct, indirect, consequential, incidental, special or economic loss (including but not limited to any loss of actual or anticipated profits, revenue, savings, production, business, opportunity, access to markets, goodwill, reputation, publicity, or use) arising from any use of or reliance on any information in this Material Safety Data Sheet.